

Discover the DITEQ Difference!



SHIBUYA RH1532 Hand-Held Pistol Grip Core Drill

Variable Speed for Hand-held or Rig Mounted Use

- 3-speed gearbox
- Inline PRCD required for wet drilling
- Multi-position removable side handle
- Two bubble levels - on side and back for precise, level drilling
- 3 LED indicators: load indicator, overload and service indicator



Fits most brands of drill rigs with industry standard squeeze mount

RH1532 and Accessories as shown:

- RH1532 drill
- Fixed base column and carriage
- Fixed bolt-on spacer
- Squeeze clamp
- Vacuum pad
- Vacuum pump
- 5" water/dust ring



The RH1532 is a multi-purpose drill that can be used with or without a drill stand. It is designed for wet or dry drilling in reinforced concrete, rock, and masonry for piping works such as air conditioners, electricity, telephone, gas, water, etc.

Bit Capacity - 4" Hand-Held
6.5" Fix Mounted



Inline GFCI

Molded case for storage and transport

Features:

- Pistol grip style handle provides balance and leverage
- 3-speed gearbox with high, medium and low speed
- Spindle shaft of 1/2" GAS female thread. For bits other than 1/2" GAS male an adapter must be used. A 5/8"-11 (P/N 150421) and a 1-1/4"-7 (P/N 150052) threaded adapter are included with the drill.
- Multi-position removable side handle
- Two-bubble levels - one on the side and the other on the back of the drill ensure level drilling
- A 3-position water connection
- Equipped with an inline GFCI (ground fault circuit interrupter) and under voltage dropout
- Equipped with electronic control device with three LED indicators:
 - 1) Green light for normal load
 - 2) Flashing red light for maximum load and a solid red light indicates overload
 - 3) An orange light advises when regular maintenance is needed.
- Circuit protector and overload switch protects drill motor by turning drill off when drill is overloaded.
- Built-in breaker switch for hand operation
- Equipped with soft start. Top speed of the spindle revolution is reached about one second after the trigger switch is pulled (hand-held mode) or the circuit protector is turned on (rig mounted mode).
- Concealed switches with circuit protector for rig mounting
- Inner gear system protects gear parts if core bit is suddenly jammed due to obstructions
- Includes molded plastic storage case with for safe, convenient storage.

Pistol Grip RH1532 Hand Drill Specifications	
MOTOR/Model No.	RH1532
AMPS/VOLTS	15/115
RPM (No Load)	800/2000/4150
RPM (Under Load)	560/1400/2900
BIT CAPACITY	(Max. Hand held) 4"
BIT CAPACITY	(Max. Fix Mounted) 6.5"
WEIGHT w/o accessories	16 lb (7.25 Kg)
PART	DR2023

Speed/Recommended Bit Diameter*

Speed Range	Hand Held	Rig Mounted	Rev/Min (No Load)	Drilling Diameter Recommendation
H	✓	✓	4150 RPM	1/2" to 1"
M	✓	✓	2000 RPM	1-1/8" to 2-3/8"
L	⊘	✓	4150 RPM	2-1/2" to 7"

*Maximum drilling diameter dependent on hardness of concrete, aggregate, size of rebar, drilling depth, etc.



1250 NW Main
Lees Summit, MO 64086
866-688-1032
877-220-4777 (fax)
www.DITEQ.com